

Titan® Commercial Wrap

Non-Woven, Non-Perforated and Certified Air Barrier



FEATURES/BENEFITS

Description

The HomeGuard® TITAN® is an advanced Building Wrap and Air Barrier Material that has been specifically engineered to provide superior building envelope performance. With premium performance in air holdout and water resistance, the TITAN® non-perforated commercial wrap minimizes air intrusion and maximizes the thermal efficiency of your wall system. TITAN® is the smart solution behind exterior claddings for commercial and residential construction, including stucco, cement, hardboard, vinyl, wood siding, brick, and stone.

Available Sizes

TITAN® Commercial Building Wrap is available in 10' x 100' rolls.

Exceptional Performance

Air Barrier & Certified Drainage Material. Non-woven and non-perforated, allowing for breathability and moisture to pass through. Preventing mold and water damage. Premium tear strength, 3 Ply construction for extreme jobsite durability, Quick & simple installation, Outstanding nail tear resistance, ensures fewer callbacks for installers and peace of mind knowing that the building envelope is protected, Excellent tape adhesion, and Breathable membrane is protected on both sides for added durability.

Warranty Information

The Lifetime Limited coverage in this warranty is designed to cover individual homeowners only. In the event that the product is installed upon property not used by individual homeowners as their residences, or for example, property owned by corporations, governments, condominiums, etc., the warranty period will be limited to 30 years. You are covered by this warranty if you live in Canada and are the original owner of the property following the construction of the structure and subsequent installation of TITAN® products purchased after September 1, 2016. EPAK warrants that our product will remain free from manufacturing defects that adversely affect its performance during the applicable warranty term if installed in strict accordance with published installation instructions, accepted industry standards, and applicable building codes in a properly designed and constructed wall system. During the initial 10-year period, EPAK will pay the full and reasonable cost of labor and provide replacement product to repair the actual area of damage caused by any defective product.

Product Information Sheet

After the initial 10-year period, labor will no longer be covered. EPAK's contribution will be limited to providing you with a replacement product or reimbursing you for the reasonable cost of replacement product at EPAK's sole discretion.

What is not covered:

This warranty covers only defects in the manufacture of TITAN® Housewrap products. It does not cover:

- Damage caused by faulty installation, abuse, improper storage, mishandling, nonstandard installation, neglect, improper maintenance, accident, modification, fire, or vandalism.
- Damage caused by prolonged exposure of the product to UV rays beyond the product's specified housewrap.ca limits.
- Damage caused by acts of God, including but not limited to lightning, flood, hail, or high winds.
- Damage caused by defects or failure of the structure.
- Damage caused by use of the product in an area containing a pool, hot tub, whirlpool, Jacuzzi, steam room, sauna, or any other area exposed to a heightened amount of moisture, humidity, or heat.
- Damage caused by foreign objects or agents, or use of materials incompatible with TITAN® products.

Properties

Review all instructions and the Material Safety Data Sheet before use. Please contact your local TITAN® Specialist should you have any questions. Product properties listed below:

Results from Testing TITAN® Commercial Building Wrap

Property	Unit	Requirement	Result
Sheet Width (tolerance)	mm	-6	pass

Physical Properties of TITAN® Housewrap

Property	Test Method	Requirement	Result
Certified Air Barrier Material	ASTM E-2178-03 Air Barrier	<0.02 L/s/m2	<0.001
Drainage Plane Channel Bulk H2O Flow	ASTM E-2273 Drainage Plane %	ICC-ES AC24 Section 6.11 (90% minimum)	Pass 93%
Durability Resistance to tear & rip underwind and joist conditions.	ASTM D-1117 Trap Tear (MD/CD)	Resistance to tearing (zipper)	15 lbs. / 12 lbs.
	ASTM- D882 MD/CD Tensile Strength (lbs.)	>20 lbs. Each MD/CD	57 lbs. / 47 lbs.
Vapor Permeable	WVTR ASTM E-96A	>35g/m2/24 hrs. (5 perms)	59 Perms
Base Weight	Tappi T-410 Basis Weight (oz/yd2)	Weight of fabric (g/m2)	130
Water Resistance Protection	AATCC-127 Water Resistance (55cm for 5 hours)	55cm H2O > 5 hours (peak resistance)	Pass (>200cm)
UV Resistance	Testing After Aging	Recommended Limits	360 Days
Flame Resistance	ASTM E-84 Flame Spread	Class A	Class A

